

# WEDA L110 (60 Hz)

## Product reference sheet


The WEDA slurry pumps are the toughest and have the largest apertures to facilitate handling of slurry with the most challenging solids. These pumps are specially designed to operate in quarries, dredging and settling ponds, dealing with abrasive media with high solids content.

Product code	Weda L110N
Installation	Portable
Discharge connection	DN150/ANSI 6 in/DIN
Hydraulic range	N - normal head
Solid handling	Max. solids 60 mm 2.4 in
Liquid temperature	max 35°C (95°F) , standard
pH of the pumped liquid	4-10
Number of poles	4
Insulation class	H
Protection class	IP68
Thermal contacts	110°C (230°F)
Cable	H07RN-F 4G35/TYPEW 4xAWG2
Cable length	20 m (65 ft)
Outer casing	CI Alloy
Impeller	Cr Alloy CI
Wear parts	Cr Alloy CI
Stator housing	CI Alloy
Strainer	CI Alloy
Shaft	Stainless steel
O-rings	Viton
Discharge connection	Steel
Bearings	Heavy Duty Bearings
Motor side seals	2 lip seals (BUNA)
Impeller side seals	5 lip seals (3 BUNA + 2 PTFE) + 1 V-RING (TPU)
Discharge	Flange
Start type	Direct-on-line


Weight and dimensions	Weda L110N
Weight (excl. cable)	2378 lb
Height	63.2 in
Width	36.8 in
Diameter	21.5 in



### Performance curve




### Power rating



Rating	3 ph
Power P <sub>1</sub>	80 kW (107 HP)
Power P <sub>2</sub>	75 kW (100 HP)
460 V	114 A
Shaft speed	1750 r.p.m.
Other voltages on request	

(2022-01-20) 2960 3650 00 rev 1 2021.06 - Subject to modifications without prior notice




# WEDA L110

## Performance sheet



### Performance curve



### Power rating

